

SK-6592 Pen-type Probe Tester



- Multifunctional Probe Tester.
- Max / Min and Difference Measurement.
- Auto Power Off prevents the battery consumption.

SPECIFICATION

Display	4000 Count LCD
Sampling Rate	2 times/sec.
Range Selection	Auto Ranging
Power Supply	One 3V CR2032 Battery.
Dimension & Weight	179(H) × 28(W) × 20(D)mm、60g
Accessories	One Black Test Lead, Battery(Installed), Carrying Case.
Optional Accessories	940 Alligator Clips.

	Range	Accuracy	Input Impedance
DCV	400mV	±0.5%rdg±3dgt	>100MΩ
	4V		Approx. 11MΩ
	40V		Approx. 10MΩ
	400V/600V	±1.0%rdg±3dgt	
ACV	4V	±1.5%rdg±5dgt	Approx. 11MΩ
	40V/400V/600V		Approx. 10MΩ
Resistance	Range	Accuracy	Test Current
	400Ω	±1.5%rdg±4dgt	<0.2mA
	4kΩ	±1.0%rdg±3dgt	< 50μA
	40kΩ		< 5μA
	400kΩ		< 0.5μA
	4MΩ	±3.0%rdg±3dgt	< 50nA

	40MΩ
	Open circuit voltage : Approx 0.44V
Other Measurement	Continuity tests, Frequency, Duty Cycle, Diode Tests, Capacitance
Other Functions	Max/Min, Difference, Display Hold, Auto Power off

- -