

SK-7622 / 7626 CE



SK-7622

SK-7626



Advanced AC Clamp Meters

SPECIFICATIONS

Display	: 4000 count LCD, Maximum reading 4301
Sampling Rate	: 2.5 times/sec
Range Selection	: Autoranging
Conductor Diameter	: ϕ 37mm Max.
Power Supply	: 1.5V R03 Batteries (x 2)
CE Mark	: CAT III 600V and EMC
Dimensions	: 203(H) \times 71(W) \times 33(D) mm
Weight	: 240g
Accessories	: 100-57 Test Leads (x 1 set) Carrying Case (x 1) 1.5V R03 Batteries (x 2)

OPTIONAL ACCESSORIES

- 880 Line Separator
- 940 Alligator Clips

SK-7622 / 7626		
	Range	Accuracy
AC Current	40A	$\pm 2.0\%rdg \pm 7dgt$
	400A	$\pm 1.5\%rdg \pm 7dgt$
	600A	$\pm 1.5\%rdg \pm 5dgt$
AC Voltage	400 / 600V	$\pm 1.0\%rdg \pm 5dgt$
Resistance	400 / 4k Ω (SK-7622)	$\pm 1.5\%rdg \pm 5dgt$
	400 / 4000 Ω (SK-7626)	
Other Measurements	Continuity Tests, MAX/MIN, Peak Hold (SK-7622), Display Hold, Auto Power Save	

- Autoranging Digital Clamp Meter.
- Dual Action Clamp Head.
- High accuracy regardless of conductor position in Clamp Head.
- MAX/MIN and Peak Hold functions (SK-7622).
- Dust-proof and Water-resistant Cases.
- CE Mark approved. EMCD and LVD (IEC 1010-1) passed.

SK-7640 CE *New!*



High-Valued Clamp Meter !

- Autoranging with Range Hold Function.
- Easy to Clamp by Beaked Clamp Head.
- Dust-proof and Water-resistant Cases.

SPECIFICATIONS

Display	: 4000 count LCD, Maximum reading 4000
Sampling Rate	: 3 times/sec
Range Selection	: Autoranging
Conductor Diameter	: ϕ 55mm Max.
Power Supply	: 9V 6F22 Battery (x 1)
CE Mark	: CAT III 600V and EMC
Dimensions & Weight	: 250(H) \times 95(W) \times 39(D) mm, 470g
Accessories	: 100-57 Test Leads (x 1 set) 1007 Carrying Case (x 1) 9V 6F22 Battery (x 1)

SK-7640			
	Range	Accuracy	
\sim A Hz / %	AC Current	400A (0~600A)	$\pm 1.5\%rdg \pm 5dgt$ (50Hz~60Hz) $\pm 3.0\%rdg \pm 5dgt$ (40Hz~1kHz)
		2000A (0~1000A)	$\pm 1.5\%rdg \pm 5dgt$ (1001A~) $\pm 3.0\%rdg \pm 5dgt$
	Frequency	5Hz~4.999kHz	$\pm 0.2\%rdg \pm 2dgt$
Duty Cycle	Not Specified		
\sim / $\bar{\sim}$ Hz / %	AC Voltage	4 / 40 400 / 600V	$\pm 1.5\%rdg \pm 5dgt$ (40Hz~400Hz) $\pm 3.0\%rdg \pm 5dgt$ (401Hz~1kHz)
	DC Voltage	400mV / 4 / 40 400 / 600V	$\pm 1.2\%rdg \pm 3dgt$
	Frequency	1Hz~100kHz	$\pm 0.2\%rdg \pm 2dgt$
	Duty Cycle	0.1%~99.9%	$\pm 2.0\%rdg \pm 2dgt$
Resistance	400 Ω	$\pm 1.5\%rdg \pm 5dgt$	
	4k / 40k / 400k Ω	$\pm 1.0\%rdg \pm 3dgt$	
	4M Ω	$\pm 3.0\%rdg \pm 4dgt$	
	40M Ω	$\pm 5.0\%rdg \pm 7dgt$	
Other Measurements	Continuity Tests, Diode Tests, Capacitance, MAX/MIN, Difference, Range Hold, Display Hold, Auto Power Save		

OPTIONAL ACCESSORIES

- 880 Line Separator
- 940 Alligator Clips



DIGITAL CLAMP METERS - AC / DC -

SK-7682 CE



Focused on High-Flexibility !

- Usable for Automotive Measurements.
- Peak Current and Peak Voltage.
- Max/Min and Difference Measurements.

SPECIFICATIONS

Display	: 4000 count LCD, Maximum reading 4050
Sampling Rate	: 3 times/sec
Range Selection	: Autoranging
Conductor Diameter	: ϕ 19mm Max.
Power Supply	: 1.5V R6P or AA Batteries (x 2)

SK-7682		
	Range	Accuracy
DC Current	40A	$\pm 1.5\%rdg \pm 3dgt$
	400A	$\pm 2.0\%rdg \pm 3dgt$ (40~200A) $\pm 4.0\%rdg \pm 3dgt$ (201~400A)
AC Current	40A	$\pm 1.5\%rdg \pm 5dgt$
	400A	$\pm 2.0\%rdg \pm 5dgt$ (36~200A) $\pm 5.0\%rdg \pm 5dgt$ (201~400A)
DC Voltage	400mV	$\pm 1.0\%rdg \pm 3dgt$
	4 / 40 400 / 600V	$\pm 1.0\%rdg \pm 2dgt$
AC Voltage	4 / 40 400 / 600V	$\pm 1.5\%rdg \pm 5dgt$
Other Measurements	Frequency, Duty Cycle, MAX/MIN, Difference, Peak Hold, Display Hold, Auto Power Off	

- | | |
|---------------------|--|
| CE Mark | : CAT III 300V and EMC |
| Dimensions & Weight | : 196(H) \times 59(W) \times 30(D) mm, 180g |
| Accessories | : 100-57 Test Leads (x 1 set)
1.5V R6P Batteries (x 2)
940 Alligator Clips (x 1 set)
1011 Carrying Case (x 1) |